

Datablad produktfamilj POWERSTAR HQI-TS

Metallhalogenlampor med kvartsteknologi för slutna armaturer



- Foyers, reception areas Factory and hall lighting with low-cost installations Exhibition halls and trade fairs Sports halls and multi-purpose halls Pedestrian zones, public squares Parks and gardens Buildings, monuments, bridges Approved only for use in enclosed luminaires Outdoor applications only in suitable luminaires

- High efficiency Uniform distribution of light Good to excellent color rendering Long lifetime Hot restrike capable UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter



Tekniska data

	Elektriska data	Fotometrisk data	Mått		Tillägg produktdata	Certifikat och Standarder	
Produktbeskrivning	ZLDV_Nominal current [AGGR]	ZLDV_Light color (designation) [AGGR]	ZLDV_Product weight [AGGR]	ZLDV_Overall length [AGGR]	ZLDV_Product remark [AGGR]	ZLDV_Energy efficiency class [AGGR]	ZLDV_Energy consumption [AGGR]
HQI-TS 400 W/D ¹⁾	4.1 A A	Daylight	88.00 g	205.60 mm	With NAV control gear	G	422.00 kWh/1000h

	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
Produktbeskrivning	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
HQI-TS 400 W/D ¹⁾	02-09-2022	4008321689191	No declarable substances contained	No declarable substances contained

¹⁾ Med NAV driftdon

HQI-TS 400 W/D

HQI-TS 400 W/D

Appliktionsråd

För mer detaljerad applikationsinformation och grafik, vänligen se produktdatablad

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4008321689191	HQI-TS 400 W/D	Transportförpackning 12	216 mm x 166 mm x 272 mm	9.75 dm ³	1418.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany