

Produktdatablad

HQI-TS 2000 W/NDL/S

POWERSTAR HQI-TS | Kort båge, utan ytterglas för slutna armaturer



Tekniska data

Elektriska data

ZLDV_PFC capacitor at 50 Hz [AGGR]	60 µF
ZLDV_Ignition voltage [AGGR]	4.0/36 kVp
ZLDV_Nominal current [AGGR]	11.3 A A

Fotometrisk data

ZLDV_Rated LLMF at 2,000 h [AGGR]	0.89
ZLDV_Rated LLMF at 4,000 h [AGGR]	0.76
ZLDV_Rated LLMF at 6,000 h [AGGR]	0.72
ZLDV_UV protection [AGGR]	No
ZLDV_Light color (designation) [AGGR]	Neutral White DE LUXE
ZLDV_Luminous flux [AGGR]	215000 lm

Mått

ZLDV_Light center length (LCL) [AGGR]	93,0 mm
ZLDV_Product weight [AGGR]	63.00 g
ZLDV_Overall length [AGGR]	187.00 mm

Temperaturer och driftsförhållanden

ZLDV_Maximum permitted pinch temperature [AGGR]	390 °C
---	--------

Livslängder

ZLDV_Lifespan B50 [AGGR]	6000 h
--------------------------	--------

Tillägg produktdata

ZLDV_Product remark [AGGR]	Not for general lighting
ZLDV_Design / version [AGGR]	Clear

Produktdatablad

ZLDV_Mercury content [AGGR]	150.0 mg
Bortskaffande enl. WEEE-direktivet	Ja

Användningsområden

ZLDV_Burning position [AGGR]	p15
ZLDV_Enclosed luminaire required [AGGR]	Yes
ZLDV_Hot restart [AGGR]	Yes

Certifikat och Standarder

ZLDV_Energy consumption [AGGR]	2123.00 kWh/1000h
--------------------------------	-------------------

Landspecifika kategorier

ZLDV_ILCOS [AGGR]	MN-2000/844-E/E/SL-K12s=36-41/187/H
-------------------	-------------------------------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4008321525499
Declaration No. in SCIP database	In work

Ljusfördelning

HQI_TS_1000W_2000W_NDL

OPERATION OF HIGH INTENSITY DISCHARGE LAMPS
WITH SEMI-PARALLEL IGNITION UNIT

Produktdatablad

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4008321525499	HQI-TS 2000 W/NDL/S	Transportförpackning g 10 Pieces Kapsel	395 mm x 165 mm x 265 mm	17.27 dm ³	1456.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.

OSRAM is distribution partner of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany