

Datablad produktfamilj

VIALOX NAV-E SUPER 4Y

Högtrycksnatriumlampor för slutna och öppna armaturer



- Streets Outdoor lighting Industrial installations
Suitable for use in open and enclosed luminaires Outdoor applications only in suitable luminaires

- Long lifetime Very high luminous efficacy Very good luminous flux maintenance throughout the life of the lamp Energy savings of up to 50 % when replacing mercury vapor lamps (HQL) Optimum energy efficiency on POWERTRONIC PTo 3DIM ECGs



Tekniska data

Produktbeskrivning	Elektriska data	Mått		Tillägg produktdata		Certifikat och Standarder	
	ZLDV_Nominal current [AGGR]	ZLDV_Product weight [AGGR]	ZLDV_Overall length [AGGR]	ZLDV_Product remark [AGGR]	ZLDV_Mercury-free [AGGR]	ZLDV_Energy efficiency class [AGGR]	ZLDV_Energy consumption [AGGR]
NAV-E 100 W SUPER 4Y ¹⁾	1.2 A A	80.00 g	180.00 mm	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable	No	F	104.00 kWh/1000h
NAV-E 250 W SUPER 4Y ¹⁾	2.95 A A	200.00 g	226.00 mm	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable		E	262.00 kWh/1000h
NAV-E 400 W SUPER 4Y ¹⁾	4.42 A A	230.00 g	285.00 mm	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable		E	419.00 kWh/1000h

Produktbeskrivning	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database
NAV-E 100 W SUPER 4Y ¹⁾	18-04-2022	4050300015774	In work
NAV-E 250 W SUPER 4Y ¹⁾	18-04-2022	4050300024387	In work
NAV-E 400 W SUPER 4Y ¹⁾	18-04-2022	4050300024394	In work

1) Viktigt: Innan du byter NAV Standard lampor i befintliga anläggningar, kontrollera att tändare är kompatibla

—	NAV-E 100 W SUPER 4Y, NAV-E 250 W SUPER 4Y, NAV-E 400 W SUPER 4Y	NAV-E 100 W SUPER 4Y, NAV-E 250 W SUPER 4Y, NAV-E 400 W SUPER 4Y
---	---	---

Appliaktionsråd

För mer detaljerad applikationsinformation och grafik, vänligen se produktdatablad

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4050300015774	NAV-E 100 W SUPER 4Y	Transportförpackning 12	380 mm x 300 mm x 203 mm	23.14 dm ³	1857.00 g
4050300024387	NAV-E 250 W SUPER 4Y	Transportförpackning 12	426 mm x 331 mm x 252 mm	35.53 dm ³	2711.00 g
4050300024394	NAV-E 400 W SUPER 4Y	Transportförpackning 12	541 mm x 416 mm x 317 mm	71.34 dm ³	4995.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Referenser / Länkar

För mer information om systemgarantivillkoren se <https://www.inventronics-light.com/multilevel-guarantees>

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany