

Produktdatablad

PLANTASTAR 250 W E40

PLANTASTAR-T | Högtrycksnatriumlampor för slutna och öppna armaturer



Tekniska data

Elektriska data

ZLDV_Ignition voltage [AGGR]	4.0/5.0 kVp
ZLDV_Nominal current [AGGR]	2.95 A A

Fotometrisk data

ZLDV_Rated LLMF at 2,000 h [AGGR]	0.98
ZLDV_Rated LLMF at 4,000 h [AGGR]	0.97
ZLDV_Rated LLMF at 6,000 h [AGGR]	0.96
ZLDV_Rated LLMF at 8,000 h [AGGR]	0.95
ZLDV_Rated LLMF at 12,000 h [AGGR]	0.94
ZLDV_Rated LLMF at 16,000 h [AGGR]	0.94
ZLDV_Rated LLMF at 20,000 h [AGGR]	0.94
ZLDV_Luminous flux [AGGR]	33000 lm

Mått

ZLDV_Light center length (LCL) [AGGR]	158,0 mm
ZLDV_Product weight [AGGR]	135.00 g
ZLDV_Overall length [AGGR]	257.00 mm

Temperaturer och driftsförhållanden

ZLDV_Maximum permitted base edge temperature [AGGR]	250 °C
---	--------

Livslängder

ZLDV_Lifespan B50 [AGGR]	32000 h
ZLDV_Lifespan B10 [AGGR]	24000 h
ZLDV_Lifespan B5 [AGGR]	20000 h

Tillägg produktdata

ZLDV_Product remark [AGGR]	Not for general lighting
ZLDV_Design / version [AGGR]	Clear
ZLDV_Mercury content [AGGR]	21.6 mg
Bortskaffande enl. WEEE-direktivet	Ja

Användningsområden

ZLDV_Burning position [AGGR]	Any
ZLDV_Enclosed luminaire required [AGGR]	No

Certifikat och Standarder

ZLDV_Energy consumption [AGGR]	270.00 kWh/1000h
--------------------------------	------------------

Landspecifika kategorier

ZLDV_ILCOS [AGGR]	ST-250-H-E40-47/257
-------------------	---------------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4008321240620
Declaration No. in SCIP database	In work

Ljusfördelning

PLANTASTAR

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4008321240620	PLANTASTAR 250 W E40	Transportförpacknin g 12 Pieces Pappkartong	266 mm x 216 mm x 342 mm	19.65 dm ³	2478.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany