

XBO 3000 W/DHS OFR

XBO DHP for digital cinema projection | Xenonlampor, kort ljusbåge



Användningsområde

- Cinema projection

Produkttegenskaper

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range




Tekniska data

Elektriska data

Märkström	105 A
Nominell watttal	300000 W
Strömstyrningsområde	77...113 A
Nominell märkspänning	290 V

Mått



Diameter	600 mm
Längd	3420 mm
Längd med sockel utan sockelstift/ansl.	302,00 mm
Kabellängd på ingångsidan	155 mm
Avstånd a / LCL	145,0 mm ¹⁾
Elektrodavstånd, kall	6,0 mm
produktvikt	59100 g
Kabellängd	1550

¹⁾ Avstånd från slutet av sockel till spets av elektrod (kallt)

Temperaturer och driftsförhållanden

Max omgivningstemperatur vid klämpunkt	230 °C
--	--------

Livslängder

Livslängd	1500 h
Service Warranty Lifetime	2000 h

Tillägg produktdata

Sockel, anod	SFaX27-9.5
Sockel, katod	SFa27-7.9

Användningsområden

Forcerad kylning	Forcerad
Brinnläge	s 15 p 15 ¹⁾

¹⁾ Vid vertikal drift, skall anoden (+) vara överst

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	05-03-2024
Primary Article Identifier	4008321199065 4008321330017 4062172030540
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	0ad1e6ac-a107-4e86-a73c-0a8cdc49edb4 468df0c2-2da9-47b4-a001-357079e3d0c0

Säkerhetsanvisningar

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172030540	XBO 3000 W/DHS OFR	Transportförpacknin g 1	500 mm x 204 mm x 204 mm	20.81 dm ³	1394.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.