

XBO 3000 W/DTS OFR

XBO DTP for digital cinema projection | Xenonlampor, kort ljusbåge


Användningsområde

- Cinema projection



Produkttegenskaper

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range




Tekniska data

Elektriska data

Märkström	105 A
Nominell watttal	300000 W
Strömstyrningsområde	77...113 A
Nominell märkspänning	290 V

Mått



Diameter	600 mm
Längd	3350 mm
Längd med sockel utan sockelstift/ansl.	285,00 mm
Avstånd a / LCL	125,0 mm ¹⁾
Elektroдавstånd, kall	4,8 mm
produktvikt	52000 g

¹⁾ Avstånd från slutet av sockel till spets av elektrod (kallt)

Temperaturer och driftsförhållanden

Max omgivningstemperatur vid klämpunkt	230 °C
--	--------

Livslängder

Livslängd	1200 h
Service Warranty Lifetime	1500 h

Tillägg produktdata

Sockel, anod	SFa30-14
Sockel, katod	SFc30-14

Användningsområden

Forcerad kylning	Forcerad
Brinnläge	s 15 p 15 ¹⁾

¹⁾ Vid vertikal drift, skall anoden (+) vara överst

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4008321645050 4008321865519 4062172030489
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	78e1128f-b105-4cf7-b75e-d67dd1f18348

Produktdatablad

Säkerhetsanvisningar

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172030489	XBO 3000 W/DTS OFR	Transportförpackning g 1	500 mm x 204 mm x 204 mm	20.81 dm ³	1316.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.