

BackLED and BoxLED mounting profiles

Tillbehör för LED-moduler för reklam och bakgrundsbelysning



Produktegenskaper

- Universellt användbar monteringsprofil för enkel eller dubbelsidiga ljuslådor
- Total längd: 2.000 mm

Produktfördelar

- Kan enkelt kortas till valfri längd
- Snabb och enkel montering av profilen med plåtskruv eller popnit
- Snabb och enkelt snäppfäste av LED-moduler, inga verktyg krävs
- Robust aluminiumprofil

Användningsområde


- Reklam och bokstäver

Tekniska data

Mått

Produktbeskrivning	produktvikt
BA -SM-MP	180,00 g

Produktskiss med nummer



BA -SM-MP

Logistikdata

Produktbeskrivning	Statistiskt varunummer
BA -SM-MP	76169990990

Environmental information
Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

Produktbeskrivning	Date of Declaration	Primary Article Identifier	Candidate List Substance 1
BA -SM-MP	18-02-2022	4052899264540	No declarable substances contained

Produktbeskrivning	Declaration No. in SCIP database
BA -SM-MP	No declarable substances contained

Datablad produktfamilj

Appliktionsråd

För mer detaljerad applikationsinformation och grafik, vänligen se produktdatablad

Försäljning och teknisk support

Försäljning och teknisk support www.osram.se

Download

Dokument	
	CAD-data 652650_CAD Daten MS Plus G15 mounting profile_IGS
	CAD-data 652651_CAD Daten MS Plus G15 mounting profile_STEP
	CAD-data PDF 652657_CAD Daten MS Plus G15 mounting profile_pdf

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
---------------	--------------------	------------------------------------	---------------------------------------	-------	------------

Datablad produktfamilj

Logistiska data

4052899264540	BA -SM-MP	Transportförpackning 24	2020 mm x 64 mm x 43 mm	5.56 dm ³	4536.00 g
---------------	-----------	----------------------------	-------------------------	----------------------	-----------

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.