

BA-TW-PL 827-865 G2

BackLED TW Plus G2 | LED-moduler för ljusreklam och bakgrundsbelysning



Produktegenskaper

- Ansluten med flexibla kablar
- Ljutfärg: dynamisk 2700 ... 6500 K
- Särskild robust inkapsling
- CE-märkt

Produktfördelar

- Flexibla programmerbara belysningsljusstämning drivet av ljusstyrningssystem
- Likformig bakgrundsbelysning av stora ytor, tack vare extremt vidvinkeloptik
- Enkel montering med M3 skruvar
- UV- och IR-fritt ljus bevarar utställningsföremålen
- Konsekvent vitt ljus (Standardavvikelse av färgmatchnings SDCM: <3) (Mac Adam step)
- 5 års garanti

Användningsområde

- Dagsljus simulering
- Span
- Butiker
- Kontor
- Museer, konstgallerier
- Permanent användning utomhus i inkapslade ljuslådor eller skyltbokstäver



Tekniska data

Elektriska data

Nominell märkspänning	240 V
Nominell wattstyrka per LED-modul	4,8 W
Accidental reverse input voltage protection up to	24 V
Inspänningsområde	23,5...24,5 V
Strömtyp	Direkt ström (DC)

Fotometrisk data

Ljuskfärg LED	vit
Ljusflöde per modulkedja	9200 lm
Ljusutbyte	958 lm/W
Ljusflöde per LED-modul	460 lm


Ljustekniska värden

Spridningsvinkel	150 °
------------------	-------

LED-modulinformation

Antal LED per modul	12
Antal LED-moduler per kedja	20
Minsta antal manövrerade LED-moduler	1

Mått



produktvikt	140000 g
Längd	1300 mm
Bredd	350 mm
Höjd	123 mm
Module length	47.5 mm

Produktdatablad

Module pitch	500 mm
--------------	--------

Temperaturer och driftsförhållanden

Temperaturområde vid Tc punkten	-25...55 °C
Förvaringstemperatur	-25...85 °C

Tillägg produktdata

Produkt anmärkning	Modules perfectly matched to OSRAM OPTOTRONIC LED drivers (see relevant table)/För aktuella fotometriska data och viktig säkerhets, installations och tillämpningsinformation, se www.osram.com/led-systems/ Samtliga tekniska parametrar som gäller för hela modulen. Mot bakgrund av den komplicerade tillverkningsprocessen för lysdioder så är de typiska värden som anges ovan för LED tekniska parametrar bara statistiska värden som inte nödvändigtvis motsvarar de faktiska tekniska parametrarna för en enskild produkt, enskilda produkter kan variera från de typiska värdena
Produkten ersätts av EAN	4052899627253

Användningsområden

Ljusregleringsområde	5...100 %
----------------------	-----------

Certifikat och Standarder


Skyddstyp	IP66
Standarder	CE
Godkännandemärkning	CE
Energy efficiency class of the contained light source	G

Logistikdata

Statistiskt varunummer	85395100000
------------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-07-2023
Primary Article Identifier	4052899452954
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained



484525_5 Year Osram Guarante
(GB)

Teknisk utrustning

- Sju typer av OPTOTRONIC 24 V elektroniska drivdon tillgängliga
- BoxLED monteringsprofil BX-MP

Databladstext

- Installation of LED modules (with power supplies) needs to be made under consideration of all valid regulations and norms.
- Installation by qualified electrician only.
- Please see the relevant application guides and instructions sheets for more detailed safety and mounting information. Additional information is available on request.
- Complies with IEC/EN 61547
- Complies with IEC/EN 61000-3-2
- Complies with EN 55015, CISPR 15
- Complies with IEC/EN 61347-1
- Complies with IEC/EN 61347-2-13
- LED modules are dimmable by means of PWM (pulse width modulation). It is recommended using the following OSRAM control gears: OPTOTRONIC OT DIM or OPTOTRONIC 24 V power supplies with integrated 1...10 V dimming interface.
- Parallel connection is mandatory for safe electrical operation. Serial connection of LED modules is strongly discouraged. Unbalanced voltage drop in serial connection can cause hazardous overload and damage the LED module.
- Electrical contact is achieved with the contact cables or the terminals of the module. Please refer to the technical data for maximum number of LED modules that can be operated on one control gear.
- In order to operate OSRAM LED modules safely, it is absolutely necessary to operate them with an electronically stabilized power supply that protects against short circuits, overload and overheating.
- In case other power supplies than OSRAM OPTOTRONIC are used, compliance to the necessary operating parameters (voltage, current, power) has to be ensured.
- Pay attention to polarity! Wrong polarity can cause destruction or malfunction of the module.
- Conducting paths on the circuit board must not be damaged or destroyed during installation.
- The LED module itself and all its components must not be stressed mechanically.
- Operation in or under water is prohibited.
- To avoid mechanical damage, the LED modules have to be attached securely to the intended mounting surface. It is recommended to avoid heavy vibration.
- In case that the LED module is equipped with a pre-mounted double-sided adhesive tape, OSRAM assumes no liability and provides no guarantee for a permanent adherence of the modules to the surface. OSRAM recommends fixation of the modules by means of suitable screws.
- Complies with IEC 61347-1 cl. 18.3, cl. 18.4, IEC 60695-2-10, IEC 60695-11-5, IEC 60695-11-10 (classification V-0)
- All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the specified typical values for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values.
- Module contains no PVC material.
- To ensure uniform illumination, a reflective matt white surface is generally recommended for all internal frame walls and back panels of light boxes.
- The module may cause noises during dimming. If a dimming operation is required, it is recommended to check the dimming operation for noises before final installation.

Download

Dokument	
	User instruction UI BackLED TW and RGBW Plus G2
	Broschyrer Technical application guide BackLED and BoxLED portfolio (EN)
	Konformitetsdeklaration BACKLED PLUS G15 CE 3320783 06 260723

Produktdatablad

	Konformitetsdeklaration 727532_Manufacturer's Declaration BackLED PLUS
	CAD-data 728688_CAD BackLED TW Plus G2.DWG
	CAD-data 728689_CAD BackLED TW Plus G2.IGS
	CAD-data 3-dim 728690_CAD BackLED TW Plus G2.STEP
	CAD-data PDF 728631_CAD BackLBackLED TW Plus G2_PDF
	Eulumdat 728626_BackLED TW Plus G2_BA-TW-PL_2700K_4052899452954
	Eulumdat 728627_BackLED TW Plus G2_BA-TW-PL_2700K+6500K_4052899452954
	Eulumdat 728628_BackLED TW Plus G2_BA-TW-PL_6500K_4052899452954.ldt
	IES data IES_BackLED TW Plus G2
	IES data IES_BackLED TW Plus G2
	IES data IES_BackLED TW Plus G2

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
---------------	--------------------	------------------------------------	---------------------------------------	-------	------------

Produktdatablad

Logistiska data

4052899452954	BA-TW-PL 827-865 G2	Transportförpackning 5	473 mm x 328 mm x 292 mm	45.30 dm ³	9777.00 g
---------------	---------------------	---------------------------	--------------------------	-----------------------	-----------

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Referenser / Länkar

For more information on the multi-level guarantee and the terms and conditions of the guarantee visit <https://www.inventronics-light.com/multilevel-guarantees>

Friskrivningsklausul

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.