OSRAM

LEDriving BASIC R10W



Product family datasheet

Technical data

	Product information		General Product Information	Electrical Data	
Product description	Product type (off- road vs. on-road)	Application (Category and Product specific)	Global order reference	Power input	Nominal voltage
LEDriving BASIC ≜ R10W	Off-road ≙ R10W	Mainly used for signal/ indicator applications	5108CW	1.44 W	12 V

				Photometric Data	Physical Attributes & Dimensions
Product description	Nominal wattage	Power input toleranc e	Test voltage	Nominal luminous flux	Lamp base
LEDriving BASIC R10W	1 W	±20 %	13.5 V	85 lm	BA15s

				Lifetime Data	
Product description	Length	Diameter	Diameter	Lifespan Lifespan B3 Tc	
LEDriving BASIC ≙ R10W	29.0 mm	19.0 mm	19.0 mm	2000 hr 2000 hr	

	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Technology	Primary article identifier	Candidate list substance 1	CAS No. of substance 1
LEDriving BASIC ≙ R10W	LED	4052899414570 4052899463141 4052899414594 4052899463356	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC ≙ R10W	The identification of	1068a570-b34f-
	the Candidate List	446b-84ce-
	substance is	Of878db5b787
	sufficient to allow	2115fbba-97ea-
	safe use of the	4065-9557-
	article.	f01077d71065
		3d88abbd-dd35-
		4bb0-bea6-
		4442158e669d
		b202dc8f-679a-
		4862-8048-
		9e2fbcf9ed99
		dcfc1ce0-153b-4d18-
		a86d-faf190a5a112

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

