LFD1000S -G2-827-04

LINEARlight FLEX Diffuse Side | – LED-moduler för professionella och industriella applikationer

Produktegenskaper

- Long operational length per single power feed up to 10 m

Produktfördelar

- IP68 protection with high performance silicone
- Reliable connection over long periods of time: IP67 connector with built-in protection against liquids penetrating through the wires into the LED strip

Användningsområde

- Skyltar och ljusreklam

© 2024, Inventronics GmbH. Alla rättigheter förbehållna. Inventronics är en licenstagare av varumärket OSRAM. OSRAM är ett varumärke som tillhör ams OSRAM.

Tekniska data


Elektriska data

Nominell wattstyrka per meter	21 W

Fotometrisk data

Ljusflöde per meter	1000 lm
SDCM Standardavvikelse färgmatchning	≤3 sdcm
Färgåtergivningsindex Ra	80

Mått



produktvikt	695,00 g
Längd	4000,0 mm
Bredd	14,1 mm
Höjd	10,80 mm

Tillägg produktdata

ID of contained light source [AGGR]	LS_TRV_286458

Logistikdata

Statistiskt varunummer	85395100000

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	07-07-2023
Primary Article Identifier	4062172271110
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1

© 2024, Inventronics GmbH. Alla rättigheter förbehållna. Inventronics är en licenstagare av varumärket OSRAM. OSRAM är ett varumärke som tillhör ams OSRAM.

Produktdatablad

Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	badac5ca-8cad-4d6b-a0d7-bd5cb6f200a9

Databladstext

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Download

	Dokument
	User instruction LINEARlight FLEX DIFFUSE
	Product Datasheet LINEARlight FLEX DIFFUSE Side_G2_Specification Sheet (EN)
	Broschyrer App Guide LINEARlight Flex Diffuse (EN)
	Broschyrer Light is freedom of design (EN)
	Certifikat VDE ENEC CERTIFICATE 40052516 160823
	Certifikat LINEARlight Flex DP UL 4413809 200622
	Eulumdat LFD1000S-G2-827-10_ldt
	IES data LFD1000S-G2-827-10_IES

© 2024, Inventronics GmbH. Alla rättigheter förbehållna. Inventronics är en licenstagare av varumärket OSRAM. OSRAM är ett varumärke som tillhör ams OSRAM.

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer.Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172271110	LFD1000S -G2-827-04	Transportförpackning 6	420 mm x 246 mm x 430 mm	44.43 dm^3	9570.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Valfria tillbehör

Produktbeskrivning	Tillbehörets namn	Tillbehörets kod
LFD1000S -G2-827-04	FX-LFDM -BEND-1000 KIT 3PCS	4062172192583

Friskrivningsklausul

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2024, Inventronics GmbH. Alla rättigheter förbehållna. Inventronics är en licenstagare av varumärket OSRAM. OSRAM är ett varumärke som tillhör ams OSRAM.