

PL-BRICK HP 3800 727 2X8

PrevaLED BRICK HP | LED modules for industry and outdoor applications



Produktegenskaper

- Module efficacy: up to 186 lm/W
- Available with color temperature: 2,200 K, 2,700 K, 3,000 K, 4,000 K, 5,700 K and 6,500 K
- Kapslingsklass: IP20

Användningsområde

- Gatubelysning
- Industri
- Områdesbelysning



Tekniska data

Elektriska data

Märkström	07 A
Strömtyp	Direkt ström (DC)
Nominell märkspänning	450 V
On-mode power [AGGR]	32.10 W
Energy consumption in on-mode [AGGR]	32.1 kWh/1000h

Fotometrisk data

Ljusutbyte	148 lm/W
Färgåtergivningsindex Ra	70
Correlated color temperature CCT [AGGR]	2700 K
Colour consistency (McAdam ellipses) [AGGR]	5
Useful luminous flux (Φuse) [AGGR]	4699 lm
Ljuskfärg LED	vit

Ljustekniska värden

Spridningsvinkel	120 °
Uppstartstid	< 01 s
Uppvärmningstid (60 %)	< 200 s

LED-modulinformation

Antal LED per modul	16
---------------------	----

Mått



produktvikt	5000 g
Height EPREL [AGGR]	8.0 mm
Length EPREL [AGGR]	224.0 mm

Produktdatablad

Width EPREL [AGGR]	50.0 mm
--------------------	---------

Temperaturer och driftsförhållanden

Förvaringstemperatur	-30...85 °C
Maximal temperatur vid tc testpunkt	85 °C
Omgivningstemperaturområde	-40...+70 °C
Temperaturbetende enl. IEC 62717	55 °C

Livslängder

Antal tändcykler	100000
Lumen maintenance factor LMF [AGGR]	96

Tillägg produktdata

Lighting technology used [AGGR]	LED
---------------------------------	-----

Certifikat och Standarder

Skyddstyp	IP20
Standarder	CE/ENEC
Energy efficiency class [AGGR]	D

Logistikdata

Statistiskt varunummer	85395100000
------------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh)	
Date of Declaration	22-09-2023
Primary Article Identifier	4062172036177
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Download

Dokument	
	CAD-data PL BRICK HP 3800 CAD DWG 300622
	CAD-data PL BRICK HP 3800 CAD STEP 300622
	CAD-data 2-dim PL BRICK HP 2850 CAD 2DIM 300622

	CAD-data 3-dim PL BRICK HP 3800 CAD 3DIM 300622
---	--

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172036177	PL-BRICK HP 3800 727 2X8	Transportförpackning 120	485 mm x 350 mm x 160 mm	27.16 dm ³	6706.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.