

HMI DIGITAL 200 W

HMI DIGITAL | Metallhalogenlampor, ensidigt socklad



Användningsområde

- Studio
- Stage
- TV

Produktfördelar

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

Produktegenskaper

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Varm omstart möjlig



Tekniska data

Elektriska data

Nominell watttal	20000 W
Nominell märkspänning	690 V
Märkström	29 A

Fotometrisk data

Nominell Ljusflöde	16000 lm
Färgtemperatur	6900 K
Färgåtergivningsindex Ra	90

Mått

Diameter	1900 mm
Längd	800 mm

Livslängder

Livslängd	200 h
-----------	-------

Tillägg produktdata

Socket	GZY9.5
--------	--------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899984110
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Produktdatablad

Säkerhetsanvisningar

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4052899984110	HMI DIGITAL 200 W	Kapsel 1	46 mm x 46 mm x 143 mm	0.30 dm ³	40.00 g
4052899984158	HMI DIGITAL 200 W	Transportförpacknin g 10	245 mm x 105 mm x 165 mm	4.24 dm ³	472.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.