

HMI DIGITAL 6000 W

HMI DIGITAL | Metallhalogenlampor, ensidigt socklad



Användningsområde

- Studio
- Stage
- TV

Produktfördelar

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

Produktegenskaper

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Varm omstart möjlig



Tekniska data

Elektriska data

Nominell watttal	600000 W
Nominell märkspänning	123 V
Märkström	55 A

Fotometrisk data

Nominell Ljusflöde	600000 lm
Färgtemperatur	6000 K
Färgåtergivningsindex Ra	90

Mått

Diameter	7500 mm
Längd	3600 mm

Livslängder

Livslängd	500 h
-----------	-------

Tillägg produktdata

Socket	GX38
--------	------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4062172005890
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	7c5a8266-8f2a-43a1-95b8-5931d68b0df1

Produktdatablad

Säkerhetsanvisningar

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172005890	HMI DIGITAL 6000 W	Transportförpacknin g 1	715 mm x 240 mm x 240 mm	41.18 dm ³	2211.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.