

Datablad produktfamilj OSRAM DULUX S LED EM

LED replacement for short CFLni, with 2-pin G23 base for CCG and AC mains operation



- Supermarkets and department stores Walkways and corridors Hotels, restaurants

- Quick, simple and safe replacement without rewiring Low energy consumption Easy relamping thanks to compact design Operation directly on 230 V AC mains possible
- Caratteristiche prodotto LED replacement for conventional compact fluorescent lamps for use in CCG luminaires or on AC mains Grado di protezione: IP20 Durata: fino a 30.000 ore Monoattacco a innesto a due pin G23 Vantaggi prodotto Sostituzione rapida, semplice e sicura senza dover ricablare Basso consumo di energia Semplice sostituzione della lampada grazie al design compatto Possibile funzionamento direttamente su rete 230 V CA Aree applicative Supermercati e grandi magazzini Passaggi pedonali e corsie Hotel, ristoranti

Datablad produktfamilj

Appliktionsråd

För mer detaljerad applikationsinformation och grafik, vänligen se produktdatablad

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany