

DALI PRO 2 IOT

DALI PRO 2 IOT | Styrenheter för belysningsystem



Produktegenskaper

- DALI-2 certified
- IoT ready with built-in gateway for remote data access
- Easy browser-based commissioning UI and Professional Software available
- Small form factor: only 6 TE (DIN rail)
- Commissioning via Ethernet/WLAN

Produktfördelar

- DALI-2 certified for improved multi-vendor interoperability
- Template based onsite commissioning via Smart device
- Building Management System integration via optional KNX interface
- Remote access for changes in the configuration from every location
- LAN Interconnect to connect up-to 8 Controllers into one network
- Rest API for connection of a 3rd party Cloud with the DALI Pro2 IoT Controller
- Automated testing and reporting of emergency lighting installations
- Daylight Simulation via scene recall and/or light sensor regulation

Användningsområde


- Rumsstyrning, golvstyrning, dagsljusberoende styrning
- Anslutning av ljus- och närvarosensorer i DALI-system
- RGB and Tunable white applications
- Konferensrum
- Kontor
- Lämplig för inomhusapplikationer
- Industri
- Ljusband
- Klassrum
- Idrottshallar

Tekniska data

Elektriska data

Nominell märkspänning	220...240 V
Nätfrekvens	50/60 Hz
Systemeffekt	20,00 W

Mått



Höjd	62,0 mm
produktvikt	247,00 g
Längd	91,0 mm
Bredd	106,0 mm

Temperaturer och driftsförhållanden

Omgivningstemperaturområde	0...+40 °C
----------------------------	------------

Användningsområden

Typ av installation	Din Rail
Scenes	512 ¹⁾
Max. connectable push button couplers	16 ²⁾
App Control	Yes (Android/ iOS)
Commissioning tool	PC Tool (Windows) / WebUI
Max. number of connected controllers	8

¹⁾ Each DALI ECG can store up to 16 light scenes.
²⁾ Max number pro DALI line. The actual number depends on the total number of DALI devices (couplers, sensors and ECGs) connected on the same DALI line

Logistikdata

Statistiskt varunummer	85371091990
------------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-08-2023
Primary Article Identifier	4062172114189
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Teknisk utrustning

- Easy browser-based commissioning UI (for smart devices)

Download

Dokument	
	User instruction DALI Pro 2 IoT
	Broschyrer Light is IoT ready - DALI PRO 2 IoT (EN)
	Konformitetsdeklaration DALI Pro 2 IoT CE 41966710 160920
	CAD-data DALI PRO 2 IoT IGS 280120
	CAD-data DALI PRO 2 IoT STEP 280120
	CAD-data 2-dim DALI PRO 2 IoT CAD2PDF 280120
	CAD-data 3-dim DALI PRO 2 IoT CAD3PDF 280120

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172114189	DALI PRO 2 IOT	Transportförpackning 20	235 mm x 199 mm x 372 mm	17.40 dm ³	5905.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Produktdatablad

Referenser / Länkar

Expert configuration software available at

▶ www.osram.com/software

Friskrivningsklausul

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.