

BA-M-HO-CP-840 G4

BackLED M-HO CP G4 | LED-moduler för ljusreklam och bakgrundsbelysning



Produktegenskaper

- Color consistency in 3 SDCM
- Patented Square Lens technology
- Wide CCT options available
- IP66 Rated

Produktfördelar

- Upgraded flux output up to 131 lm
- Uniform light pattern design for 100-150 mm light-box depth
- Over-molding technology for optimal protection



Tekniska data

Elektriska data

Nominell märkspänning	120 V
Nominell wattstyrka per kedja	48.00 W
Nominell wattstyrka per LED-modul	1.2 W
Accidental reverse input voltage protection up to	13 V
Inspänningsområde	12...13 V
Strömtyp	Direkt ström (DC)

Fotometrisk data

Färgtemperatur	4000 K
Färgåtergivningindex Ra	80
Ljutfärg (angiven)	Neutral vit
Ljutfärg LED	Neutral white
Ljusflöde per modulkedja	5120 lm
Ljusflöde per LED-modul	131 lm
Ljusutbyte	109 lm/W
Luminous flux per LED module at Ta 25 °C	131 lm
Luminous flux per chain at Tc 25 °C	5240 lm


Ljustekniska värden

Spridningsvinkel	155 °
------------------	-------

LED-modulinformation

Antal LED per modul	3
Antal LED-moduler per kedja	40
Minsta antal manövrerade LED-moduler	1

Mått



Längd	81680 mm
Bredd	138 mm
Höjd	68 mm
produktvikt	21000 g
Module length	47.5 mm
Module pitch	200 mm

Temperaturer och driftsförhållanden

Temperaturområde vid Tc punkten	-30...70 °C ¹⁾
Förvaringstemperatur	-30...85 °C

¹⁾ Exceeding the maximum ratings will reduce expected life time or destroy the LED strip. / Vid T_c punkten

Livslängder

Livslängd	50000 h ¹⁾
-----------	-----------------------

¹⁾ L70/B50 vid 70 °C

Tillägg produktdata

ID of contained light source [AGGR]	LS_SHZ_600369
Produkten ersätts av EAN	4052899504721

Användningsområden

Ljusregleringsområde	1...100 %
----------------------	-----------

Certifikat och Standarder

Energiförbrukning	48 kWh/1000h
Skyddstyp	IP66

Produktdatablad

Standarder	enl. EN 55015/enl. EN 61547/Acc. to EN 62031/Acc. to IEC 62778/Acc. to IEC 62471/enl. IEC 61347-1/Acc. to IEC 60598-1
Godkännandemärkning	CE / BIS
Energy efficiency class of the contained light source	F

Logistikdata

Statistiskt varunummer	85395100000
------------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	09-08-2023
Primary Article Identifier	4062172183475
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	58ba5a12-ce11-4f91-8d5b-de79e7e3d887

Download

Dokument	
	User instruction BackLED SM CP G4 UI OSRAM
	Broschyrer Technical application guide BackLED and BoxLED portfolio (EN)

Produktdatablad

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172183475	BA-M-HO-CP-840 G4	Transportförpackning 50	435 mm x 435 mm x 310 mm	58.66 dm ³	11782.00 g

— Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Valfria tillbehör

Produktbeskrivning	Tillbehörets namn	Tillbehörets kod
BA-M-HO-CP-840 G4	BA -MP-M-CP-2	▶ 4062172168410

Friskrivningsklausul

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.