Product family datasheet

LEDriving SL P21W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Cool White



Replaces conventional P21W lamps Easy upgrade to LED technology with

plug & play solutions



Guarantee³

Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21W

LEDriving SL P21W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Product information			General Product Information		Electrical Data		
Product description	Product type (off- road vs. on-road)	Application (Category and Product specific)		Global order reference		Power Nominal voltag input		
LEDriving SL ≙ P21W	Off-road ≙ P21W	Mainly used for signal/ indicator applications	7506DV	VΡ	1.8 W	12 V		
				Photometric	Data	Physical A Dimension	Attributes &	
Product description	Nominal watt	tage Power input toleranc e	Test voltage	Nominal luminous flux		Lamp base		
LEDriving SL \doteq P21W	1 W	±25 %	13.5 V	160 lm		BA15s		
						Lifetime [Data	
Product description	Length	Diameter		Diameter		Lifespan B3	Lifespan Tc	
LEDriving SL \doteq P21W	52.5 mm	25.0 mm		25.0 mm		1500 hr	4000 hr	
	Capabilities	Environmental & Ro Information accordi (REACh)			n (EC) 190	7/2006		
Product description	Technology	Primary article identifier	Candio substa			S No. of substance		
LEDriving SL \triangleq P21W	LED ¹⁾	4062172348652 4062172152181 4062172401210 4062172408318	Lead		7439-9	92-1		

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving SL \doteq P21W	The identification of	4b523b49-273b-
	the Candidate List	43fa-a900-
	substance is	dfef06fdea31
	sufficient to allow	e75f732e-151e-
	safe use of the	4392-9807-
	article.	f15711d460b4
		cbc40782-6f5e-4a73-
		ad3f-4f03b28c1891
		431a14a2-e6f5-451f-
		b379-4763b7bc7850

¹⁾ Light-emitting diode lamp

Product family datasheet

Download Data

File
User instruction GPRS_Safety symbols instructions
Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.