

## LF3000 -G3-827-03 L1

LINEARlight FLEX High Power IP00 | LED-moduler för professionella och industriella applikationer



### Produktegenskaper

- Flexibel klippbar LED list

### Produktfördelar

- Color uniformity better than 2 SDCM on the entire LED strip and between strips
- Stort urval av ljusfärger
- Enkel montering på många släta ytor tack vare självhäftande tejp på baksidan

### Användningsområde

- Valvbelysning
- Tak integration



Tekniska data

Elektriska data

|                                                   |                   |
|---------------------------------------------------|-------------------|
| Nominell märkspänning                             | 24,0 V            |
| Strömtyp                                          | Direkt ström (DC) |
| Nominell wattstyrka per meter                     | 23,7 W            |
| Märkeffekt                                        | 71,10 W           |
| Inspänningsområde                                 | 23...25 V         |
| Accidental reverse input voltage protection up to | 25 V              |

Fotometrisk data

|                                      |          |
|--------------------------------------|----------|
| Färgåtergivningsindex Ra             | >80      |
| Ljusflöde per meter                  | 3000 lm  |
| Totalt användbart ljusflöde          | 9000 lm  |
| Ljusutbyte                           | 127 lm/W |
| SDCM Standardavvikelse färgmatchning | ≤3 sdcn  |
| Ljuskfärg (angiven)                  | 2700 K   |
| Färgtemperatur                       | 2700 K   |

Ljustekniska värden

|                        |          |
|------------------------|----------|
| LED pitch              | 14.29 mm |
| Spridningsvinkel       | 120 °    |
| Uppstartstid           | < 0,5 s  |
| Uppvärmningstid (60 %) | < 0,50 s |

LED-modulinformation

|                            |    |
|----------------------------|----|
| Antal LED per meter        | 70 |
| Antal LED per minsta enhet | 7  |

Mått



|                         |                      |
|-------------------------|----------------------|
| Längd                   | 3000,0 mm            |
| Längd – minsta enheten  | 100,0 mm             |
| Kabellängd              | 500,0                |
| produktvikt             | 46,00 g              |
| Ledningsarea ingångsida | 0.51 mm <sup>2</sup> |
| Bredd                   | 8,00 mm              |
| Höjd                    | 1,40 mm              |

Temperaturer och driftsförhållanden

|                                  |                            |
|----------------------------------|----------------------------|
| Temperaturbetende enl. IEC 62717 | 55 °C                      |
| Temperaturområde vid Tc punkten  | -20...90 °C <sup>1)</sup>  |
| Omgivningstemperaturområde       | -20...+50 °C <sup>2)</sup> |
| Förvaringstemperatur             | -40...80 °C                |

<sup>1)</sup> Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

<sup>2)</sup> Rated ambient temp. 25°C/Providing that temperature at Tc point is below max value during operation/Temperature ramping for environmental testing acc. to IEC 62717, 1K/min

Livslängder

|                    |         |
|--------------------|---------|
| Beräknad livslängd | 60000 h |
| Nominell livslängd | 60000 h |
| Ljusnedgångsfaktor | 0,70    |
| Antal tändcykler   | 15000   |

Tillägg produktdata

|                                     |               |
|-------------------------------------|---------------|
| Produkten ersätts av EAN            | 4062172143073 |
| ID of contained light source [AGGR] | LS_TRV_217938 |

Användningsområden

Produktdatablad

|                       |       |
|-----------------------|-------|
| Lowest bending radius | 20 mm |
| Self-adhesive         | Ja    |
| With connection set   | Nej   |
| With end piece        | Nej   |

Certifikat och Standarder

|                                                       |                                                               |
|-------------------------------------------------------|---------------------------------------------------------------|
| Standarder                                            | CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750 |
| Skyddstyp                                             | IP00                                                          |
| Energy efficiency class of the contained light source | F                                                             |

Logistikdata

|                        |             |
|------------------------|-------------|
| Statistiskt varunummer | 85395100000 |
|------------------------|-------------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                                                                                                    |
|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Date of Declaration                                                   | 07-07-2023                                                                                         |
| Primary Article Identifier                                            | 4062172263757                                                                                      |
| Candidate List Substance 1                                            | Lead                                                                                               |
| CAS No. of substance 1                                                | 7439-92-1                                                                                          |
| Safe Use Instruction                                                  | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration No. in SCIP database                                      | 7efd1c5b-fd8d-4261-8209-d6a7c714111b                                                               |

Teknisk utrustning

- Förenklad anslutning med matchande tillvals CONNECTsystem
- Snabb installation med valfri SLIM TRACK System
- Perfekt anpassade till OPTOTRONIC 24 V elektroniskt förkopplingsdon

Databladstext

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Download

|          |
|----------|
| Dokument |
|----------|

Produktdatablad

|                                                                                     |                                                                 |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------|
|    | User instruction<br>LINEARlight FLEX POWER                      |
|    | Product Datasheet<br>LINEARlight Flex Power Specification Sheet |
|    | Broschyrer<br>Light is freedom of design (EN)                   |
|    | Certifikat<br>EAC Certificate                                   |
|    | Certifikat<br>UL Certificate                                    |
|    | Certifikat<br>ENEC10_VDE Certificate                            |
|    | Certifikat<br>CB TEST CERTIFICATE DE1-57844                     |
|    | Konformitetsdeklaration<br>LF HP G3 CE 4160937 280623           |
|    | Konformitetsdeklaration<br>LF HP G3 CE 3420012 03 071119        |
|   | Konformitetsdeklaration<br>EU Declaration of conformity         |
|  | Konformitetsdeklaration<br>Manufacturer declaration             |
|  | Eulumdat<br>LF3000-G3-827-03 L1 V2 LDT 28032022                 |
|  | IES data<br>LF3000-G3-827-03 L1 V2 IES 28032022                 |

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

| Produktnummer | Produktbeskrivning   | Förpackningsenhet (Styck/Enhet) | Dimensioner (längd x bredd x höjd) | Volym                | Bruttovikt |
|---------------|----------------------|---------------------------------|------------------------------------|----------------------|------------|
| 4062172263757 | LF3000 -G3-827-03 L1 | Transportförpackning 8          | 241 mm x 195 mm x 205 mm           | 9.63 dm <sup>3</sup> | 1301.00 g  |

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Valfria tillbehör

| Produktbeskrivning   | Tillbehörets namn             | Tillbehörets kod |
|----------------------|-------------------------------|------------------|
| LF3000 -G3-827-03 L1 | CONN-FLEX -2P-050 KIT 10PCS   | ▶ 4062172179591  |
| LF3000 -G3-827-03 L1 | CONN-FLEX -2P-200 KIT 10PCS   | ▶ 4062172179614  |
| LF3000 -G3-827-03 L1 | CORNER-FLEX -4P-003 KIT 10PCS | ▶ 4062172179638  |
| LF3000 -G3-827-03 L1 | CORNER-FLEX -4P-015 KIT 10PCS | ▶ 4062172179676  |
| LF3000 -G3-827-03 L1 | LTS-SLIMTRACK -2000 KIT 5 PCS | ▶ 4062172207300  |
| LF3000 -G3-827-03 L1 | FX-QMS-G1 -TU15H6-300         | ▶ 4052899448865  |
| LF3000 -G3-827-03 L1 | FX-QMS-G1 -TU15H6W3-300       | ▶ 4052899448889  |
| LF3000 -G3-827-03 L1 | FX-QMS-G1 -TU16H12W3-300      | ▶ 4052899448988  |
| LF3000 -G3-827-03 L1 | FX-QMS-G1 -TU16H12-300        | ▶ 4052899448964  |
| LF3000 -G3-827-03 L1 | FX -SC08-G2-CT4PJ             | ▶ 4052899464858  |

Produktdatablad

|                      |                          |                 |
|----------------------|--------------------------|-----------------|
| LF3000 -G3-827-03 L1 | FX-QMS-G1 -TU16H12LS-300 | ▶ 4052899449046 |
|----------------------|--------------------------|-----------------|

Friskrivningsklausul

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.