

OPTOTRONIC Intelligent – DALI NFC TW

Compact constant current LED driver – Dimmable



Användningsområde

- Klassrum
- Konferensrum
- Dagsljussimulation för fönsterlösa rum
- Installation i nödbelysningsystem enligt IEC 61347-2-13, bilaga J
- Lämplig för inom- och utomhus SELV installationer

Produktfördelar

- Control of standard white or Tunable White light acc. DALI device type 8 (DT8)

Produktegenskaper

- Nätfrekvens: 0 Hz | 50 Hz | 60 Hz
- Matningsspänning: 220...240 V
- Usable as DT6 (2-channel) or DT8 (Tunable White) driver

Datablad produktfamilj

Appliktionsråd

För mer detaljerad applikationsinformation och grafik, vänligen se produktdatablad

Databladstext

- Electrical connections between the two output channels are not allowed.
-

Försäljning och teknisk support

Försäljning och teknisk support www.osram.se

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.
