

CONN-FLEX -2P-200 KIT 10PCS

White 2pin Flexible LED strips Connector | Tillbehör för flexibla LED-lister

Produktegenskaper

- Quick and easy installation
- Compatible with TEC Flex




Produktfördelar

- Enkel installation, inga verktyg eller lödning krävs (CONNECTsystem)
- Minskad installationstid (CONNECTsystem)
- Kan vara ansluten till den främre delen av modulen eller vid delningspunkter (CONNECTsystem)
- Låg profil (CONNECTsystem)

Tekniska data

Mått



Längd	2019 mm
produktvikt	3523 g
Bredd	104 mm
Höjd	40 mm

Tillägg produktdata

Produkten ersätts av EAN	4052899464766
--------------------------	---------------

Logistikdata

Statistiskt varunummer	85366990990
------------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	03-08-2022
Primary Article Identifier	4062172179614
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Download

Dokument	
	User instruction Connection System for LINEARlight Flex & TEC Flex IP00

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172179614	CONN-FLEX -2P-200 KIT 10PCS	Transportförpackning 10	337 mm x 270 mm x 400 mm	36.35 dm ³	2307.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.