

LTS-SLIMTRACK -2000 KIT 5 PCS

Minimal surface slim profile 15x10mm | external cover | Tillbehör för flexibla LED-lister



Produktegenskaper

- Compatible with TEC Flex

Produktfördelar

- Aluminium profil robust och korrosionsbeständiga tack vare anodisering

Användningsområde

- Tak integration
- Recessed lighting
- Valvbelysning
- Hyll- och möbelbelysning

Tekniska data

Mått



Längd	2000 mm
produktvikt	33000 g
Bredd	146 mm
Höjd	95 mm

Logistikdata

Statistiskt varunummer	76042990900
------------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	25-04-2022
Primary Article Identifier	4062172207300
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Download

Dokument	
	Product Datasheet Specification Sheet LTS-SLIMTRACK-2000

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172207300	LTS-SLIMTRACK -2000 KIT 5 PCS	Transportförpackning 4	50 mm x 105 mm x 2040 mm	10.71 dm ³	2066.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Valfria tillbehör

Produktbeskrivning	Tillbehörets namn	Tillbehörets kod
LTS-SLIMTRACK -2000 KIT 5 PCS	LTS-MOUNTINGBRACKET KIT 20 PCS	4062172212090
LTS-SLIMTRACK -2000 KIT 5 PCS	LTS-COVER -CLEAR-2000 KIT 5 PCS	4062172207348
LTS-SLIMTRACK -2000 KIT 5 PCS	LTS-COVER -OPAL-2000 KIT 5 PCS	4062172257466
LTS-SLIMTRACK -2000 KIT 5 PCS	LTS-COVER -OPAL-S-2000 KIT 5 PCS	4062172207324
LTS-SLIMTRACK -2000 KIT 5 PCS	LTS-ENDCAP -CLEAR KIT 20 PCS	4062172212151
LTS-SLIMTRACK -2000 KIT 5 PCS	LTS-ENDCAP -OPAL-S KIT 20 PCS	4062172212137

Friskrivningsklausul

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.