

LEDDriving HLM EASY GEN 2 H7/H18



Ultra compact LED replacement for conventional H7/H18 high and low beam lamps

“Socket Design” – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an easy installation



Cool White color temperature

Better visibility thanks to daylight effect



LED high and low beams lamps with plug & play system: no adapters and caps needed.

With its socket-based solution, the OSRAM LEDDriving HLM EASY GEN 2 retrofits provide an ultra-compact LED replacement of conventional H7/H18 high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDDriving HLM EASY GEN 2 high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for motorcycles with the respective halogen lamp types.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Tekniska data

Produktbeskrivning	Elektriska data			Fotometrisk data	
	Max. effekt	Nominell märkspänning	Nominell watttal	Ljusflöde	Ljusflöde, tolerans
LEDDriving HL EASY GEN 2 ≙ H7/H18	16.0 W	12 V	16 W	2000 lm	±25 %

Produktbeskrivning	Fysiska egenskaper och dimensioner	Livslängder	Information om miljö och regelverk Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Diameter	Livslängd Tc i timmar	Primär identifiering av artikel	Deklarationsnummer i SCIP-databasen
LEDDriving HL EASY GEN 2 ≙ H7/H18	20.0 mm	1000 hr	4062172420341	I arbete

Download

Dokument	
	User instruction Säkerhets symboler
	Brochures LEDriving Retrofits - Exchange overview (EN)

Säkerhetsanvisningar

Application advice:

For more detailed application information and graphics please see product datasheet and user manual.

Applikationsråd

För mer detaljerad applikationsinformation och grafik, vänligen se produktdatablad

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.