OSRAM

LEDinspect SLIM MAX1000

Inspectionlights





Dimmer Switch Individually adjustable brightness levels with up to 1000 lm



1000 Lumen Bright, white LED light and uniform light distribution



Multi-Angle Light Output High flexibility due to individual adjustment of the light beam



2-year-OSRAM guarantee* Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



Light is versatile

This high-quality inspection light is perfect for professional and private use. With an integrated dimmer, you can select the appropriate brightness level with up to 1000lm for the task at hand with the SLIM MAX 1000. The ultra slim design combined with multi-angle positioning gives maximum flexibility and adjustability to give light exactly where needed. The SLIM MAX 1000 is rechargeable and cordless with Li-ion battery and can therefore provide constant light output. The lamp has an operating time of up to 1.5h with high light output or up to 10,5h with low light output. Charging cable and mains adaptor are included in the scope of supply. In accordance with the IP protection class IP65,

Product family datasheet | LEDinspect SLIM MAX1000 © 2025, OSRAM GmbH. All rights reserved.

this inspection light has protection against the ingress of dust and water and is tested for impact resistance in accordance with IK06. This inspection light has an integrated hook and magnets for hands-free work, making it ideal as a light for manual tasks, car repairs and for everyday use. In addition, OSRAM grants a 2-year guarantee on this product*

Technical data

	Product information General Product Information		uct	Electrical Data			
Product description	Application (Category and Product specific)	Global order reference		Nominal wattage		Nominal voltage	
INSPECTION LAMP	LED inspection lights	LEDIL410		9 W		3.7 V	
	Photometric Data				Physica Dimens	al Attributes & sions	
Product description	Color temperature	Nominal luminous flux		Light color LED	Product weight		
INSPECTION LAMP	6000 K	1000 lm		White	340.00 g		
						LED module information	
Product description	Length	Width	Height			Number of LEDs per module	
INSPECTION LAMP	365.0 mm	50.0 mm		50.0 mm		2	
	Colors & materials	Lifetime Data	Addition	Additional product data			
Product description	Base color	Guarantee	Type of Battery		Number of included batteries		
INSPECTION LAMP	Black / Orange	2 years	Recharg	eable	1		
		Capabilities		Certificates & Lo standards		Logistical data	
Product description	Scope of battery	Technology	IK Class		Watt hour per battery		
INSPECTION LAMP	Yes	LED	IK06		9.49		
	Environmental & Regu Information according	•		(EC) 1907/2006	(REACh)		
Product description	Candidate list substance 1	CAS No. of substance 1		Safe use instruction		Declaration no. in SCIP database	
INSPECTION LAMP	Lead	7439-92-1		The identification of the Candidate List substance is sufficient to allow safe use of the article.		99d5749d-0f33-4ebf- 9ff7-b17da405d236	

Download Data

 File

 Ser instruction

 GPRS_Safety symbols instructions

Legal advice

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.