

LEDDriving SL T5

Ideal replacement for any vehicle



Suitable for various vehicle interior and exterior applications

Available in Cool White



Replaces conventional T5 lamps (e.g. ECE W2.3W)

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for T5 (e.g W2.3W)

LEDDriving SL T5 replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional T5 lamp bases (e.g. ECE W2.3W). In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description | Electrical Data | | | | | Photometric Data |
|---------------------------------------|-----------------|-----------------|-----------------|-----------------------|--------------|-----------------------|
| | Power input | Nominal voltage | Nominal wattage | Power input tolerance | Test voltage | Nominal luminous flux |
| LEDDriving SL \triangleq W2.3W (T5) | 0.25 W | 12 V | 0 W | $\pm 20\%$ | 13.5 V | 25 lm |

| Product description | Physical Attributes & Dimensions | | | |
|---------------------------------------|----------------------------------|---------|----------|----------|
| | Lamp base | Length | Diameter | Diameter |
| LEDDriving SL \triangleq W2.3W (T5) | W2x4.6d | 16.5 mm | 6 mm | 6 mm |

| Product description | Lifetime Data | | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|---------------------------------------|---------------|-------------|---|----------------------------|
| | Lifespan B3 | Lifespan Tc | Primary article identifier | Candidate list substance 1 |
| LEDDriving SL \triangleq W2.3W (T5) | 750 hr | 2000 hr | 4062172254687 4062172401838 | Lead |

| Product description | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|---------------------------------------|------------------------|--|---|
| LEDDriving SL \triangleq W2.3W (T5) | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 0c5665af-69f3-4cb5-92d6-53765a15bdac 82245377-8731-4a13-8ef4-9051d2f6d948 |

Download Data

| File | |
|---|---|
|  | User instruction GPRS_Safety symbols instructions |
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.