

LEDDriving SL W5W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional W5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for W5W

LEDDriving SL W5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional W5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| | Product information | | General Product Information | Electrical Data | |
|------------------------------|--|-------------------------------------|-----------------------------|-----------------|-----------------|
| Product description | Application (Category and Product specific) | Product type (off-road vs. on-road) | Global order reference | Power input | Nominal voltage |
| LEDiving SL \triangleq W5W | Mainly used for signal/ indicator/ interior applications | Off-road \triangleq W5W | 2825DWP | 1.12 W | 12 V |

| | | | | Photometric Data | Physical Attributes & Dimensions |
|------------------------------|-----------------|-----------------------|--------------|-----------------------|----------------------------------|
| Product description | Nominal wattage | Power input tolerance | Test voltage | Nominal luminous flux | Lamp base |
| LEDiving SL \triangleq W5W | 1 W | $\pm 10\%$ | 13.5 V | 70 lm | W2.1x9.5d |

| | | | | Lifetime Data | |
|------------------------------|---------|----------|----------|---------------|-------------|
| Product description | Length | Diameter | Diameter | Lifespan B3 | Lifespan Tc |
| LEDiving SL \triangleq W5W | 25.4 mm | 10.0 mm | 10.0 mm | 1500 hr | 4000 hr |

| | Capabilities | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | | |
|------------------------------|-------------------|---|----------------------------|------------------------|
| Product description | Technology | Primary article identifier | Candidate list substance 1 | CAS No. of substance 1 |
| LEDiving SL \triangleq W5W | LED ¹⁾ | 4062172408295 4062172348638 4062172352055 4052899620810 4062172401258 | Lead | 7439-92-1 |

| Product description | Safe use instruction | Declaration no. in SCIP database |
|------------------------------|--|--|
| LEDiving SL \triangleq W5W | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 6f026af0-500d-4f2d-bd6a-1166bb294d48 64465242-4712-4f51-8663-313005785df0 34b9f3a2-0f08-481c-8c6e-9e87347ba1cf 87230ce2-265b-4740-ae73-4ad692d83c04 d493a7ba-1e50-4adf-97d4-fe52b1e7a9c4 |

¹⁾ Light-emitting diode lamp

Download Data

| File | |
|---|---|
|  | User instruction GPRS_Safety symbols instructions |
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.