Product family datasheet

OSRAM

LCD Remote Screen



Compatible with both 12V and 24V Modified and Pure Sine Wave POWERinvert PRO inverters Works with all OSRAM POWERinvert PRO inverters




Multifunction Readings1. DC Voltage Input2. AC Voltage Output3. Continuous Wattage4. Amp hour Full picture of how the inverter is performing and the state of health the vehicle's battery

OSPAN



6m of Cable






Complemented by the LCD frame (OINVFRM) for secure housing

Bracket provides additional protection to the screen and secure fixing

Accessories for inverter





Product family datasheet

Technical data

	Product information	Product information Physical Attributes & Dimensions		
Product description	Application (Category and Product specific)	Length	Width	Height
LCD Remote Screen OINVLCD	Inverter accessory	70.0 mm	27.8 mm	99.5 mm
	Dimensions & weight	Certificates & standards	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	Input Cable Gauge / Length	Standards	Primary article identifier	Candidate list substance 1
LCD Remote Screen OINVLCD	6 m	CE-EMC / ROHS / WEEE / E- Mark	4052899631113	Lead

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LCD Remote Screen OINVLCD	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	363f17b5-80dd- 4aa6-8573- ec6b4071bd21

Product family datasheet

Safety advice

Tested and certified to the relevant EMC and LVD Directives.

Legal advice

CE ApprovedRoHS and WEEE Approved.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.